(19) World Intellectual Property **Organization**

International Bureau



(43) International Publication Date 30 June 2005 (30.06.2005)

PCT

(10) International Publication Number WO 2005/059931 A1

- (51) International Patent Classification?: 4/30, 4/38, H01B 17/50, 17/54
- H01G 4/224,
- (21) International Application Number:

PCT/SE2004/001923

(22) International Filing Date:

17 December 2004 (17.12.2004)

(25) Filing Language:

Swedish

(26) Publication Language:

English

(30) Priority Data:

0303482-4

19 December 2003 (19.12.2003)

- (71) Applicant (for all designated States except US): ABB Technology Ltd [CII/CII]; Affoltemstrasse 44, CII-8050 ZÜRICH (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): DRUGGE, Birger [SE/SE]; Engelbrektsplan 2, S-SE-722 16 VÄSTERAS (SE), MOOD, Johan [SE/SE]; Bruksgatan 3 D. S-SE-771 31 LUDVIKA (SE). DOWLING, Kenneth [SE/SE]: Säbyholms Gård, S-SE-197 91 BRO (SE), LAIHO-NEN, Sari [SE/SE]; Föreningsgatan 20 A. S-SE-722 18 VÄSTERÄS (SE). OLSSON, Carl-Olof [SE/SE]; Karlsgatan 32 B, S-SE-722 14 VÄSTERÄS (SE). HOLM-GREN, Tommy [SE/SE]; Körsbürsstigen 3, S-SE-771 43 LUDVIKA (SE).


- (74) Agent: ABB AB; Legal & Compliance/Intellectual Propeny, S-SE-721 78 VÄSTERÄS (SE).
- (81) Designated States funless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FL GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN. TR. TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW. GH. GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO. SE, SI, SK, TR). OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: POWER CAPACITOR



(57) Abstract: A power capacitor comprising at least one capacitor element (2a-2d) enclosed in a container (1, 22-22c). wherein the container is of a material which substantially comprises a first polymer material. Further, the container is cylindrical and provided in its surface with creepage distanceextending protrusions (23-23e) of a second polymer material. The protrusions are formed with respect to their thickness and radial length so as to cool the capacitor. In a method for manufacturing such a power capacitor, a substantially cylindrical container is made of a material which substantially comprises a first polymer material. The container (1, 22-22c) is provided on its envelope surface with creepage distance-extending protrusions (23-23e) of a second polymer material and the capacitor elements are encapsulated in the container.